



PROTECTSOL 512CA

Water Displacing Thin Film Corrosion/ Rust Preventive

PROTECTSOL 512CA is an oil-based water-displacing corrosion/rust preventive for use on ferrous and non-ferrous metal surfaces. Protectsol 512CA provides up to 6 months indoor storage protection against corrosion & rust with an ease of application. Protectsol 512CA forms a thin, non-staining transparent and highly protective film. Protectsol 512CA will quickly separate alkaline water from metal surfaces.

CLEANABILITY

PROTECTSOL 512CA can be removed with simple alkaline cleaners such as American Research Products AMERICLENE 20

PRODUCT FEATURES & BENEFIT

- SCAQMD Rule 1144 Compliant.
- Meets and exceeds Mil-C-16173 Grade 3 Federal Specification.
- Meets and exceeds Mil-C-22235 Federal Specification for corrosion preventive.
- De-waters all water miscible solutions such as coolants, cleaners, rinses.
- Protectsol 512CA can be used safely on non-ferrous and ferrous metal surfaces

PHYSICAL PROPERTIES

Odor: Light Solvent

Color: Light Brown Color

Density: 6.9 lbs/gal

Specific Gravity: 0.84

Flashpoint: 212° COC ASTM D92

VOC Content: 305 grams/per liter ASTM 1868-10